



PETRON PLUS™ FORMULA 7



PETRON PLUS™ FORMULA 7 HEAVY-DUTY MULTI-PURPOSE FLEET, & INDUSTRIAL GREASE

▶ **PART NO.'S: 00550-14oz, 00550-35lbs, 00550-120lbs, & 00550-400lbs**

TECHNICAL DATA SHEET

Petron Plus™ Formula 7 Heavy-Duty Multi-Purpose Fleet & Industrial Grease is the latest technological advance in Over Based Calcium Sulfonate Complex Grease.

Petron Plus™ Formula 7 Heavy-Duty Multi-Purpose Fleet & Industrial Grease is recommended for severe applications in many industries. It is particularly suitable for high speed bearings and centralized lubrication systems.

Petron Plus™ Formula 7 Heavy-Duty Multi-Purpose Fleet & Industrial Grease is recommended for use in automotive as well as extreme pressure applications in constructions, mining, oil field, agricultural, logging and hauling industries. This product is suitable anywhere where a shear stable, high load carrying, corrosion resistant grease is required.

Petron Plus™ Formula 7 Heavy-Duty Multi-Purpose Fleet & Industrial Grease will provide excellent performance in severe high temperatures applications, with light or heavy loads, and under wet or dry conditions

Petron Plus™ Formula 7 Heavy-Duty Multi-Purpose Fleet & Industrial Grease is compatibility with a wide variety of seal materials, such as Nitrile, Viton and Neoprene.

This product has a 550°+ Dropping point, a Timken OK load of 65 lbs. and a weld point of 620 kg.

APPLICATIONS:

1. Heavy-Duty Fleets.
2. Commercial & industrial applications.
3. Marine applications.
4. Lake or salt water applications.
5. Automotive and industrial applications.
6. Construction equipment.
7. Where a NLGI 2 grease is required.
8. Meets NLGI GC-LB Standards.
9. As a 5th Wheel Grease.
10. Mining applications.

FEATURES:

1. A Over Based Calcium Sulfonate Complex.
2. NLGI 2
3. Extremely High Temperature Performance.
4. Dropping Point of 550°F+.
5. Timken OK Load of 65 lbs.
6. Four Ball EP Weld of 620 kg.
7. Excellent water resistance.

BENEFITS:

1. Contains no heavy metals.
2. Long life grease.
3. Reduced maintenance costs.
4. Heavy Load Carrying Capabilities..
5. Highly water resistance.

Kevin Lambert, Petron Plus MN
18039 Rawlins St NW
Elk River, MN 55330

612-363-7176

petronplumn.com

TYPICAL SPECIFICATIONS:

PETRON PLUS™
FORMULA 7
HEAVY-DUTY MULTI-PURPOSE FLEET, & INDUSTRIAL GREASE

Part No., 00550-14oz, 00550-35lbs, 00550-120lbs, 00550-400 lbs
Thickener,	Calcium Sulfonate Complex
NLGI, Consistency Grade, ASTM D-217,	2
Texture,	Smooth, Tacky
Dropping Point, °F, ASTM D-2265,	550+
PENETRATION		
Unworked, ASTM D-217,	265-295
Wheel Bearing Leakage, GM, ASTM D-1263,	5.0 Max
Water Washout, @ 175°F, mass %, Max, ASTM D-1265,	3.0
Timken OK Load, lbs, ASTM D-2509,	65
Load Wear Index, ASTM D-2596,	65
Four Ball EP Weld, kgf, ASTM D-2596,	620
Four Ball Wear Scar, mm, ASTM D-2266,	0.40
USS Mobility Test @ 0°F, gm/min., USS DM 43,	13.6
USS Mobility Test @ -20°F, gm/min., USS DM 43,	4.0
DI Rust Protection, ASTM D-1743,	Pass
OIL VISCOSITY		
@ 40°C, cSt, ASTM D-445,	220
Color,	Aqua Green

Available in 14 ounce tubes, 35 lbs. pails, 120 lbs. keg, & 400 lbs. drums.

Distributed By:

September, 2014

Warranty: All products purchased from Petron Plus Global, Inc., (PPGI) are subject to terms and conditions set out in the contract, order acknowledgment and/or bill of lading. PPGI warrants only that its product will meet those specifications designated as such herein or in other publications. All other information supplied by PPGI is considered accurate but is furnished upon the express condition that the customer shall make its own assessment to determine the product's suitability for a particular purpose. No warranty is expressed or implied regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose, or that the use of such other information or product will not infringe any patent.